# A Resource Description Language with Vagueness Support for Multi-Provider Cloud Networks



Gregor Schaffrath, **Stefan Schmid**, Ishan Vaishnavi, Ashiq Khan, Anja Feldmann Telekom Innovation Laboratories (Berlin) & DoCoMo Eurolabs (Munich), August, 2012

# A Resource Description Language with Vagueness Support for Multi-Provider Cloud Networks



Gregor Schaffrath, **Stefan Schmid**, Ishan Vaishnavi, Ashiq Khan, Anja Feldmann Telekom Innovation Laboratories (Berlin) & DoCoMo Eurolabs (Munich), August, 2012

# Vision: Virtual Networking Cloud Resources.



#### Cloud computing is a big success! But what is the point of clouds if they cannot be accessed?



# **CloudNets: Next Natural Step for Virtualization!**

#### **Success of Node Virtualization**

- a.k.a. end-host virtualization
- VMWare revamped server business
- VM = basic unit in datacenters...
- … hardly any physical resources!
- VM = flexible allocation, migration...

#### **Trend of Link Virtualization**

- VLANs
- Software Defined Networks (SDN), OpenFlow, ...

## Unified, fully virtualized networks: CloudNets

"Combine networking with heterougeneous cloud resources (e.g., storage, CPU, ...)!"



# **Virtualization Benefits**

Virtualization = Decoupling of services / CloudNets from physical infrastructure (substrate network)



Therefore:

- Can allocate CloudNet flexibly subject to specification (flexible service deployment)
- CloudNets can cohabit same substrate network in isolation
- Abstracts heterogeneous resources
- CloudNets can even run different protocol stacks!

## Some Use Cases.

## "VPN++"

<u>Goal</u>: Fully specified CloudNet mapping constraints (e.g., end-points for a **telco**), but with **QoS guarantees** (e.g., bandwidth) along links



# Datacenters



## Spillover/Out-Sourcing



## **Migration**

<u>Goal</u>: Move with the sun, with the commuters, (QoS) allow for **maintenance**, avoid roaming costs...: e.g., **SAP/game/translator server, small CDN server...** 





# $\cdot \cdot T$

Lelekom Innovation Laboratories

# Example of CloudNet Embedding.

Connecting Providers (Geographic Footprint).



# **Business Roles.**

CloudNet opens new business roles!

We propose that properties and prices are negotiated between economic roles.



### Roles

- Service Provider (SP): uses CloudNets to offer its services (e.g., value-added application CloudNet, or transport CloudNet)
- Virtual Network Operator (VNO): Installs and operates CloudNet over topology provided by VNP, offers tailored connectivity service, triggers cross-provider migration (by setting requirements), ...
- Virtual Network Provider (VNP): "Broker"/reseller that assembles virtual resources from different PIPs to provide virtual topology (no need to know PIP, can be recursive, ...)
- Physical Infrastructure Provider (PIP): Owns and manages physical infrastructure

QoS from PIP up to VNO or service provider: **accounting** via complete **set of contracts**! (unlike "sending party pays")



Telekom Innovation Laboratories

# CloudNets require a flexible resource description language: FleRD!

FleRD is used in our CloudNet prototype...

## FleRD Uses.

**ICCCN 2012** 

 Communicate CloudNets, substrate resources and embeddings to business partners or customers:





• Store embedding state internally:

Telekom Innovation Laboratories

# FleRD Requirements.

- Support all kinds of node (storage, computation, ...) and link (latency, bw, full-duplex/asymmetric, ...) resources (heterogeneity)
- Extensible, allow for syntactic changes over time, no need for global agreement on semantic values
- Facilitate resource leasing and allow PIPs to open abstract views on their substrate
- Allow for vagueness and omission: customers are unlikely to specifiy each CloudNet detail (e.g., KVM or Xen is fine, outsource to any European cloud provider): this opens ways for optimization (exploiting flexibilities)!
- Allow for aggregation of resources (business secret?)
- Non-topological requirements (e.g., wordsize compatibility)



# FleRD Design Principles.

- Based on generic objects (semantic value only of local interest): Network Elements (NEs)
- Interconnected via Network Interfaces (NI)
- Note: NEs can be links, can model multicast links by connecting NIs accordingly!
- NE properties are described by attribute-value-pairs: Resources (e.g., amount of storage) and Features (e.g., CPU flags)
- Predicates over features (e.g., for white or black listing)
- Constraint groups allows to specify non-topological properties
- Mapping can be recursive
- Attribute space hierarchical (compare e.g. to SNMP, like «link/symmetric/bw»)



## Problem:

- Support all kinds of node (storage, computation, ...) and link (latency, bw, full-duplex/asymmetric, ...) resources (heterogeneity)
- Extensible, allow for syntactic changes over time, no need for global agreement on semantic values
- Facilitate resource leasing and allow PIPs to open abstract views on their substrate
- Allow for vagueness and omission: customers are unlikely to specifiy each CloudNet detail (e.g., KVM or Xen is fine, outsource to any European cloud provider): this opens ways for optimization (exploiting flexibilities)!
- Allow for aggregation of resources (business secret?)
- Non-topological requirements (e.g., wordsize compatibility)

# Solution:

- Based on generic objects (semantic value only of local interest): Network
   Elements (NEs) interconnected via Network Interfaces (NI)
- NE properties are described by attribute-value-pairs: Resources (e.g., amount of storage) and Features (e.g., CPU flags)
  - Predicates over features (e.g., for white or black listing)
- Constraint groups allows to specify non-topological properties
  - Mapping can be recursive
- Attribute space hierarchical (compare e.g. to SNMP)



# A Use Case: Web Service.

Service Provider asks for Web Service:

- VHost1 and VHost2 (i.e., service distributed over two processes)
- VHost1 in US or Canada (white listing)
- VHost2 vague
- Connection not via Afghanistan (black listing)
- 2-redundant path



# How is request embedded on physical infrastructure? Stages can all be described with FleRD!

- Different stages (could be merged if same role but just to illustrate concepts...)
- Build Overlay0 and Overlay1 out of request
- Mapping layer to annotate configuration details (e.g., VLAN tags) and to keep mapping state
- Substrate layer: Underlay0 and Underlay1

# Overlay0.



XML version (excerpt): Features of VHost 1

Lelekom Innovation Laboratories

# Overlay1.



- Expand request to make more concrete
- Add two explicit links / paths
- Virtual hosts have RAM and HDD resources
- Virtual links have up and down stream requirements
- Multiplex components (splitters) are added to split the link in disjoint paths
- Constraints are added to ensure disjoint paths

# Mapping Layer.



- To annote config details (e.g., VLAN tags) or keep mapping state
- One-to-many vs many-to-many mappings?
- Optional «bridge» between OL and UL
- Virtual links are expanded into three virtual hops (one in US, one in Canada, one between)

# Underlay1.



- Reason for two underlays: keep both logical structure of the substrate (as used for mapping) and representation of physical setup
- Underlay1 still contains VPN tunnel and shared NFS
- VHost1 is mapped to SHost3 and Splitter1 is mapped to VHost1, VHost2 and Splitter2 are mapped to VHost2...
- Upper virtual link realized via 3 tunnel segments (via external physical providers Provider2 and Provider3)
- Lower virtual link within given provider
- NFS still logically attached to substrate nodes

# Underlay0.



- Physical situation of considered provider (Provider1)
- NFS hosted only by one host (SHost3), plus link to access NFS from SHost1
- Tunnel counterparts not visible

# **Related Work.**

### Rspec (PlanetLab, ProtoGENI)

 Resources not modelled as separate referencable entities, not extensible and unsuitable in multi-layer and multi-provider setting

#### NDL+OWL: ontology for automated reasoning

- not flexible and syntactic overhead
- OCCI (Open Grid Forum)
  - no multi-layers support

### DEN-ng: business-driven network management

- explicit distinction between virtual and physical network, no multi-layer support
- VN-SLA: service level specifications
  - no mappings

### VxDL: virutal execution infrastructure description

- no mappings
- NOVI
  - no resource mappings
- NDL
  - no support for efficient multi-home links, no omission, or black and white listing, ...



# Conclusion.

- FleRD is used in our own CloudNet prototype implementation
- Prototype based on VLANs
- Flexibilities exploited via Mixed Integer Program embeddings





Migration demo

## The Project Website.

#### **Combining Clouds with Virtual Networking**

### The CloudNet Project

Internet Network Architectures (INET) TU Berlin / Telekom Innovation Labs (T-Labs) Contact: Stefan Schmid



News

Overview People Magazines Publications Demo Talks/Posters

#### News

- · Watch on YouTube: migration demonstrator video!
- We are looking for students and interns with good algorithmic background to contribute to Virtu! Contact us
  for more details or have a look at some open topics.

#### Project Overview

CloudNets are virtual networks (VNets) connecting cloud resources. The network virtualization paradigm allows to run multiple CloudNets on top of a shared physical infrastructure. These CloudNets can have different properties (provide different security or QoS guarantees, run different protocols, etc.) and can be managed independently of each other. Moreover, (parts of) a CloudNet can be migrated dynamically to locations where the service is most useful or most cost efficient (e.g., in terms of energy conservation). Depending on the circumstances and the technology, these migrations can be done live and without interrupting ongoing sessions. The flexibility of the paradigm and the decoupling of the services from the underlying resource networks has many advantages; for example, it facilitates a more efficient use of the given resources, it promises faster innovations by overcoming the ossification of today's Internet architecture, it simplifies the network management, and it can impove service performance.

We are currently developing a prototype system for this paradigm (currently based on VLANs), which raises many scientific challenges. For example, we address the problem of where to embed CloudNet requests (e.g., see [1] for online CloudNet embeddings and [2] for a general mathematical embedding program), or devise algorithms to migrate CloudNets to new locations (e.g., due to user mobility) taking into account the

# Collaborators and Publications.

## People

- T-Labs / TU Berlin: Anja Feldmann, Carlo Fürst, Johannes Grassler, Arne Ludwig, Matthias Rost, Gregor Schaffrath, Stefan Schmid
- Uni Wroclaw: Marcin Bienkowski
- Uni Tel Aviv: Guy Even, Moti Medina
- NTT DoCoMo Eurolabs: Group around Wolfgang Kellerer

## Publications

- Prototype: VISA 2009, ERCIM News 2012, **ICCCN 2012**
- Migration: VISA 2010, IPTComm 2011, Hot-ICF 2011
- Embedding: ICDCN 2012 (Best Paper Distributed Computing Track)





## Contact.

•••



#### Dr. Stefan Schmid

Telekom Innovation Laboratories Ernst-Reuter-Platz 7, D-10587 Berlin E-mail: stefan@net.t-labs.tu-berlin.de Project website: <u>http://www.net.t-labs.tuberlin.de/~stefan/virtu.shtml</u>



